



CUE-D75

73Wh Li-ion V-Mount Battery with D-Tap

The CUE-D75 is IDX's most economical Lithium Ion V-Mount battery. Providing 73Wh of DC power, the CUE-D75 can withstand 4.9A / 59W loads—perfect for low power consuming cameras and accessories. A built-in D-Tap connection capable of taking a 50W load is available for powering accessories. The CUE-D75 features 4 Power Indicator LED to accurately display the battery capacity status. Built to the highest standards of quality and reliability, the CUE-D75's new internal pack design cradles each cell securely to enhance the reliability and safety of the battery.

CUE-D75 Product Features:

- **Lithium Ion battery** designed to meet Japans stringent PSE safety regulations for enhanced mechanical and electrical safety.
- **Manufactured in co-operation with Sanyo**, the world's premier supplier of Lithium Ion cells.
- **73Wh capacity** with the ability to handle 4.9A / 59W loads.
- **(1) D-Tap DC output (unregulated)** connector is capable of taking a 50W load within the maximum draw of 59W.
- **4 Power Indicator LEDs** are located on the side for a quick and accurate capacity readout.
- **Weighing only 1.37 lbs.** the CUE-D75 is lightweight, compact and durable, ideal for small profile cameras and accessories.
- **Battery circuit protection** ensures the CUE-D75 is fully protected against common causes of misuse, guarding against over-charge, over-discharge, and over-current.
- **The highest grade Lithium Ion cells** are used to ensure the CUE-D75 is one of the most reliable batteries on the market.
- **Unrestricted** spare CUE-D75 batteries are approved for carry-on airline baggage under IATA regulations. For further clarification please contact IDX.
- **The CUE-D75 is fully compatible** with all ENDURA V-Mount chargers and accessories.
- **Environmentally friendly** and recyclable.

*Endura
Cue*



Technical Specification

Battery Capacity:

73Wh (14.8V, 4.9Ah)

Max. Output Voltage:

16.8V DC

Nominal Voltage:

14.8V DC

Maximum Discharge Current:

4.9A / 59W

End Voltage

12V

Battery Protection:

Over charge
Over discharge
Over current

Ambient Temperature:

To charge:

32°F ~ 104°F / 0°C ~ 40°C

To discharge:

-4°F ~ 113°F / -20°C ~ 45°C

To store:

-32°F ~ 104°F / -35°C ~ 40°C

Dimensions:

3.82(W) x 5.75(H) x 1.51(D) inches
97(W) x 146(H) x 38(D) mm

Weight:

1.37 lbs. / 621g approx.

E & OE

IDX System Technology, Inc.
19001 Harborgate Way, Suite 105
Torrance, CA 90501 U.S.A.
Telephone: (310) 328-2850
Fax: (310) 328-8202

IDX Technology Europe, Ltd.
Unit 9, Langley Park,
Waterside Drive, Langley,
Berkshire, SL3 6EZ, ENGLAND.
Telephone: +44 (0)1753 547692
Fax: +44 (0)1753 546660



20140416

