




Comparison Charts
Title: 12V Battery Solutions for 5V/7.4V/8.4V Cameras
Release Date: 5/11/15



Combine the following V-Plate + DC Cable combinations in order to power your 5V/7.4V/8.4V cameras with IDX 12V Battery Solutions

| | Adaptors | | Camera Power Consumption (Wh) | Estimated ENDURA Battery Run Time | | | | |
|------------------|------------|----------|-------------------------------|-----------------------------------|----------------|----------------------------|---------------------------|--------------|
| | P-V Plate | DC Cable | | DUO-150/ CUE-D150 146Wh | ELITE 136Wh | DUO-95/ CUE-D95 91Wh | E-HL9 / E-HL9S 87Wh | E-7S 68Wh |
| SONY | | | | | | | | |
| HXR-NX5U | P-V284 | C-SONC | 8.4 | 17.4 | 16.2 | 10.8 | 10.4 | 8.8 |
| HXR-MC50U | | | 15 | 9.7 | 9.1 | 6.1 | 5.8 | 4.5 |
| HVR-Z5U/Z7U | | | 7.1 | 20.6 | 19.2 | 12.8 | 12.3 | 9.7 |
| HVR-V1U | | | 6.8 | 21.5 | 20.0 | 13.4 | 12.8 | 10 |
| HVR-Z1U/FX1 | | | 8.4 | 17.4 | 16.2 | 10.8 | 10.4 | 8.5 |
| NEX-FS-100 | | | 5.6 | 26.1 | 24.3 | 16.3 | 15.5 | 9.7 |
| PANASONIC | | | | | | | | |
| AG-HMC150 *D | P-V257 | C-PANAVC | 9.8 | 14.9 | 13.9 | 9.3 | 8.9 | 6.9 |
| AG-HMC70 *D | | | 8.5 | 17.2 | 16.0 | 10.7 | 10.2 | 8 |
| AG-HMC40 *D | | | 5.8 | 25.2 | 23.4 | 15.7 | 15.0 | 11.7 |
| AG-AC160A | | | 11.8 | 12.4 | 11.5 | 7.7 | 7.4 | 5.8 |
| AG-AF100 | | | 12.4 | 11.8 | 11.0 | 7.3 | 7.0 | 5.5 |
| AG-HVX200 *D | P-V257 | C-PANCP2 | 14 | 10.4 | 9.7 | 6.5 | 6.2 | 4.8 |
| AG-HPX170 *D | | | 13.8 | 10.6 | 9.9 | 6.6 | 6.3 | 4.9 |
| AG-HPX250 / 255 | | | 17 | 8.6 | 8.0 | 5.4 | 5.1 | 4 |
| AG-3DA1 | | | 17 | 8.6 | 8.0 | 5.4 | 5.1 | 4 |
| AG-DVX100 *D | | | 7.2 | 20.3 | 18.9 | 12.6 | 12.1 | 9.4 |
| JVC | | | | | | | | |
| GY-HM100 *D | P-V257 | C-JVCC | 7.2 | 20.3 | 18.9 | 12.6 | 12.1 | 9.4 |
| GY-HM600 / 650 | TA-PV2J650 | | 12 | 12.2 | 11.3 | 7.6 | 7.3 | 5.7 |
| CANON | | | | | | | | |
| XF-100 / 105 | P-V257 | C-CANC | 6.1 | 23.9 | 22.3 | 14.9 | 14.3 | 11.1 |
| XF-300 | | | 9 | 16.2 | 15.1 | 10.1 | 9.7 | 7.5 |
| XL-H1 *D | | | 7.4 | 19.7 | 18.4 | 12.3 | 11.8 | 9.1 |
| XH-G1 *D | | | 7.3 | 20.0 | 18.6 | 12.5 | 11.9 | 9.1 |
| XH-A1 *D | | | 6.9 | 21.2 | 19.7 | 13.2 | 12.6 | 9.8 |
| EOS 5D / 7D | P-V257 | C-EOSC | 13.0 | 11.2 | 10.5 | 7.0 | 6.7 | 5.2 |
| C100 | A-E2EOSC | | 8.1 | 18.0 | 16.8 | 11.2 | 10.7 | 8.4 |
| C300 | | | 20.9 | 7.0 | 6.5 | 4.4 | 4.2 | 3.3 |
| C500 | | | 23.9 | 6.1 | 5.7 | 3.8 | 3.6 | 2.8 |

* D = discontinued products

IDX System Technology, Inc.
 19001 Harbortgate Way, Suite 105
 Torrance, CA 90501 USA
 Telephone: (310) 328-2850
 Fax: (310) 328-8202

For further information, email us: idx.usa@idx.tv or visit our website www.idxtek.com
 IDX reserves the right to change the specifications contained herein without notice.

